

Table 1-1

	MASS WEIGHT	Aperture Distance (APD)	Elevation				Windage			Extension			Material			Colours	Included Accessories	
			Adjustment Model	Length	Adjustable Range	Adjustment Increments	Tilt Adjustment	Adjustable Range	Adjustment Increments	Compatible Apertures	Length	Adjustable Range	Adjustment Increments	Elevation	Windage Unit			Extension
Carbon Model	204g	MAX 248m MIN 83mm	Screw Drive with No-Lock Quick Adjust Function	123mm (approx. 4.8")	approx. 97mm	1/24" per revolution (approx. 1mm) 1/480" per click (approx. 0.05mm)	adjustable	5.4mm	1/32" per revolution (approx. 0.8mm) 1/640" per click (approx. 0.04mm)	No.8-32 threaded sight pins	233mm (approx. 9")	6.5" (approx. 165mm)	1/2" (approx. 12.7mm)	6000 series aluminium alloy	6000 series aluminium alloy	Carbon Fiber	Black Silver Blue Red Gold Pink Green Orange	Soft Sight Case No.10-24 mount screws Hex Wrenches 1.5mm/2mm/3mm Blank sight tape Instructions Sheet Warranty card, parts diagram User registration card
Standard Model	210g	MAX 248m MIN 96mm									225mm (approx. 9")	6" (approx. 152mm)	1" (approx. 25.4mm)			6000 series aluminium alloy		